



R410A Domestic range

CLASSIC 5-25

MODEL	Applications	Power	COP ¹ EER ²	EXW	
				230 V 1/N/PE~	400 V 3/N/PE~
Clausius classic H 5-25	Heating and DHW	5 to 25 kW	5.01 ----	230 V 1/N/PE~	400 V 3/N/PE~
Clausius classic H 5-25 PC	Heating and DHW Passive cooling	5 to 25 kW 6 kW	5.01 ----	230 V 1/N/PE~	400 V 3/N/PE~
Clausius classic H 5-25 DS	Heating and DHW Desuperheater	5 to 25 kW ----	5.01 ----	230 V 1/N/PE~	400 V 3/N/PE~
Clausius classic H 5-25 PC DS	Heating and DHW Passive cooling Desuperheater	5 to 25 kW 6 kW ----	5.01 ----	230 V 1/N/PE~	400 V 3/N/PE~
Clausius classic HC 5-25	Heating and DHW Active cooling	5 to 25 kW 6 to 28 kW	5.01 6.5	230 V 1/N/PE~	400 V 3/N/PE~
Clausius classic HC 5-25 PC	Heating and DHW Active cooling Passive cooling	5 to 25 kW 6 to 28 kW 6 kW	5.01 6.5	230 V 1/N/PE~	400 V 3/N/PE~
Clausius classic HC 5-25 DS	Heating and DHW Active cooling Desuperheater	5 to 25 kW 6 to 28 kW ----	5.01 6.5	230 V 1/N/PE~	400 V 3/N/PE~
Clausius classic HC 5-25 PC DS	Heating and DHW Active cooling Passive cooling Desuperheater	5 to 25 kW 6 to 28 kW 6 kW ----	5.01 6.5	230 V 1/N/PE~	400 V 3/N/PE~

1) According to EN14511, 0/-3, 30/35.

2) According to EN14511, 7/12, 30/35.